



General		
article description	ECO Fan+ 4550	ECO Fan+ 5400
article number	723560	723565
required mains frequency	50 Hz	50 Hz
weight (excl. grills)	9.2 kg (unpackaged) 10.6 kg (packaged)	10.4 kg (unpackaged) 11.8 (packaged)
length	275 mm	275 mm
inlet side diameter	537 mm	537 mm
outlet side diameter	504 mm	504 mm
packaged dimensions (LxWxH)	56 x 56 x 31 cm	56 x 56 x 31 cm
permissible ambient temperature	0 .. 40 °C	0 .. 40 °C
IP code of motor	IP54 in accordance with EN/IEC 60529	
maximum noise level at a 2 m distance	60 dB(A)	63 dB(A)
air displacement (unobstructed)	4,600 m ³ /h	5,450 m ³ /h
throw	41 m	48 m
maximum row spacing between fans	16 m	16 m
rpm	1,415 rpm	1,420 rpm
mains voltage	230 V	230 V
current consumption, nominal	0.5 A	0.8 A
current consumption, maximum	0.8 A	1.5 A
electrical capacity	120 W	160 W
energy efficiency	31.30%	32.30%
degree of efficiency	42	43
power supply cable core cross section (optional)	0.75 mm ²	0,75 mm ²
Priva Fan in combination with Priva Air-Tube		
air displacement at a back pressure of 30Pa	3,835 m ³ /h	4,620 m ³ /h
tube diameter	505 mm	505 mm
maximum row spacing between air tubes	16 m	16 m