

	AZUD DISC FILTER MODULAR 100					
	130 Micron 3/4" (20mm)	130 Micron 1" (25mm)	130 Micron 1 1/4" (32mm)	130 Micron 1 1/2" (40mm)	130 Micron 1 1/2" Super (40mm)	130 Micron 2" (50mm)
	Code# FL/AZ17L1A120	Code# FL/AZ17L1B120	Code# FL/AZ17L1C120	Code# FL/AZ17L1D120	Code# FL/AZ17L1E120	Code# FL/AZ17L1BF120
Material	Black Thermoplastic	Black Thermoplastic	Black Thermoplastic	Black Thermoplastic	Black Thermoplastic	Black Thermoplastic
Inlet Thread Size	20mm BSPM	25mm BSPM	32mm BSPM	40mm BSPM	40mm BSPM	50mm BSPM
Outlet Thread Size	20mm BSPM	25mm BSPM	32mm BSPM	40mm BSPM	40mm BSPM	50mm BSPM
Max. Inlet Flow (Lpm)	83	100	166	233	333	416
Max. Inlet Pressure (kPa)	800	800	800	800	800	800
Filter Type	120 Mesh	120 Mesh	120 Mesh	120 Mesh	120 Mesh	120 Mesh
Replacement Filter Code #	FL/AZ17RLG100	FL/AZ17RLG100	FL/AZ17RLG101	FL/AZ17RLG101	FL/AZ17RLG102	FL/AZ17RLG102
<p>Maximum flow rates are determined at 35kPa head loss (130 micron). Flow rates higher than the maximum recommended will increase head losses.</p> <p>Flow rates are dependent on water quality and filtration grade. NOTE: Clean water flow rate at 20kPa head loss - 130 micron.</p>						