

## RAIN-CLIK™

To prevent water waste, built-in Quick Response™ technology instantly shuts down irrigation as soon as it starts raining.

### Key Benefits

- Instant Quick Response rain shutoff and freeze shutoff at 3°C
- Adjustable vent ring allows for shorter or longer reset period
- Includes gutter bracket and wall mount with wireless models
- Maintenance-free design with integrated battery for wireless models
- Rugged polycarbonate housing and metal extension arm
- Compatible with most normally open or normally closed irrigation controllers

### OPERATING SPECIFICATIONS

- Quick Response:
  - Time to turn off irrigation system: approximately 2 to 5 minutes for Quick Response
  - Time to reset Quick Response: approximately 4 hours under dry, sunny conditions
  - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 7 m of 0.5 mm<sup>2</sup> sheathed, two-conductor, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 243 m line of sight from sensor to receiver
- Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

### Sensor: Rain/Freeze



**RAIN-CLIK/RFC**  
(with mounting arm)  
Height: 6 cm  
Length: 18 cm



**SGM**  
Height: 1.2 cm  
Length: 7.6 cm



**WR-CLIK/WRF-CLIK**  
(with mounting arm)  
Height: 7.6 cm  
Length: 20 cm



**Wireless Receiver**  
(with mounting hardware)  
Height: 8.3 cm  
Length: 10 cm



**Wireless Sensor Guard**  
(with mounting hardware)  
Height: 7 cm  
Length: 9.5 cm  
Depth: 3.2 cm



**Wireless Receiver Guard**  
(with mounting hardware)  
Height: 12.7 cm



Model	Description
RAIN-CLIK	Wired Rain-Clik sensor
RFC	Wired Rain/Freeze-Clik sensor
WR-CLIK	Wireless Rain-Clik sensor and receiver
WRF-CLIK	Wireless Rain/Freeze-Clik sensor and receiver
RAIN-CLIK-NO	Wired Rain-Clik Sensor, Normally Open

### User-Installed Options

Model	Description
SGM	Optional gutter mount (included with WR-CLIK and WRF-CLIK)
WS-GUARD	Vandal-resistant wireless sensor guard for flat surfaces or pole mounting (order sensor separately)
WR-GUARD	Vandal-resistant wireless receiver guard for pedestal mounting (order receiver separately)
WR-CLIK-R	Wireless Rain-Clik receiver