





## 10" HOUSING A B 185 mm 355 mm

C

185 mm



GENERAL INFO

FOR INTERNAL AND EXTERNAL LISE

D

610 mm

## Large Diameter Filter Housings, 4.5" Diameter

The Puretec LD Series is designed for large capacity filtration in high flow rate and heavy sediment applications. It helps to improve water quality and protects your plumbing system from damage and premature clogging due to sediment build-up. The latest technology in filter housings engineering, constructed using reinforced polypropylene that ensures years of trouble-free service. Puretec LD Series housings are also compatible with a broad range of chemicals.

SPECIFICATIONS						
Model Number:	LD1025	LD1025K	LD1040	LD2025	LD2040	LD2040K
Description:	10" Filter housingsilver	10" Filter housing kit, silver includes bracket and housing wrench	10" Filter housing silver	20" Filter housing silver	20" Filter housing silver	20" Filter housing kit, silver includes bracket and housing wrench
Flow Rate:	80 Lpm	80 Lpm	85 Lpm	160 Lpm	180 Lpm	180 Lpm
Min/Max Temperature:	0 - 52 °C	0 - 52 °C	0 - 52 °C	0 - 52 °C	0 - 52 °C	0 - 52 °C
Min/Max Pressure:	0 - 875* kPa	0 - 875* kPa	0 - 875* kPa	0 - 875* kPa	0 - 875* kPa	0 - 875* kPa
Connection:	1"	1"	1½"	1"	1½"	1½"
Warranty:	1 year^	1 year^	1 year^	1 year^	1 year^	1 year^

Important Note: Use only genuine Puretec replacement cartridge. ^1 year warranty is 1 year parts and labour. Protect from freezing. \*Where line pressure exceeds 500 kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards. (Ref. AS/NZS 3500.1:2021, Clause 3.3.4).

## FEATURES & BENEFITS

- Internal and external use to suit different applications.
- 1 year warranty^.
- Large diameter filter housing for larger flow rate.
- Quick and easy installation.

SPARE PARTS & ACCESSORIES (SOLD SEPARATEL	-Y)
Single Bracket Kit :	LDBK
Double Bracket Kit:	LDBK2
Replacement O-Ring:	LDOR
Housing Wrench:	LDW