

GENERAL INFO

Aftermarket Compatible Cartridges

The Puretec Aftermarket CC series range means you can enjoy the benefits of Puretec's quality filtration in your existing system. Designed to reduce rust, dirt, sediment, chlorine, algae and chemicals leaving beautiful, fresh drinking water.

FEATURES & BENEFITS

- Reduces chlorine, pesticides, bad taste, odours, organic chemicals, dirt, and rust.
- Quick-change hygienic cartridge.
- Retains essential minerals and fluoride.



CARTRIDGE SPECIFICATIONS

Model	Size	Micron Rating*	Min/Max Pressure (kPa)	Capacity	Operating Temperature	Suits
CC-ACZ8110	9½"	5	68 - 520 kPa	7,500 L	2 - 55°C	Aqua Cooler Z-8110
CC-QAP8R	12"	0.5	68 - 520 kPa	11,300 L	2 - 55°C	3M Aqua-Pure AP8000 (AP8112), IBC A112-SQC, Comcater CCE105
CC-QAP9CO	9"	1	68 - 520 kPa	10,000 L	2 - 55°C	3M Aqua-Pure AP9300 (AP9351), HF15
CC-QZ937-02	9"	0.2	68 - 520 kPa	4,000 L	2 - 55°C	ZIP/Zenith 93701, 93702, 93704 & 93706
CC-QAP9R	13½"	1	68 - 520 kPa	22,000 L	2 - 55°C	3M Aqua-Pure AP9000 (AP9112), AP9100+ (AP9950+), AP9400, HF25-S, CWFAP9112, C-Cyst-FF, ZIP 92321
CC-QCBF2	10"	0.5	68 - 520 kPa	1,900 L	2 - 55°C	Shurflo RV-QDRF-A, Omnifilter R1100R, CBF2, SFM3, Pentek QC10-CBRR
CC-QEVCB5K	11"	5	68 - 520 kPa	10,000 L	2 - 55°C	Everpure 2CB5-K
CC-QEVCB5S	11"	5	68 - 520 kPa	10,000 L	2 - 55°C	Everpure 2CB5-S, Everpure 2CB-GW
CC-QEVCB5S-MX	14"	5	68 - 520 kPa	20,000 L	2 - 55°C	Everpure 4CB5-K, 4CB5-S, S104
CC-QMQC	10"	5	68 - 520 kPa	7,500 L	2 - 55°C	Davey MQC SP/MQCPP
CC-QZ937-3	9"	3	68 - 520 kPa	6,500 L	2 - 55°C	ZIP/Zenith 93703, 93705
CC-QZP28	10"	5	68 - 520 kPa	7,500 L	2 - 55°C	ZIP 28001, 28002, 28004, 28005, Birko 1211047 & 1311068
CC-QZP51	8"	5	68 - 520 kPa	11,000 L	2 - 55°C	ZIP/Zenith 51000, 52000, 53000, 3M Cuno CS-51, Bosch CS-52, 5586605, 5553629, 5553606, EVOLFLTR10, AP3961137, Whirlpool WHKFR-PLUS
CC-QZP91	9"	5	68 - 520 kPa	9,000 L	2 - 55°C	ZIP/Zenith 91241
CC-QZP91-05	9"	0.5	68 - 520 kPa	9,000 L	2 - 55°C	ZIP/Zenith 91240
CC-QZP9102G	9"	0.2	68 - 520 kPa	4,500 L	2 - 55°C	ZIP 91289, 91290, 91291, 3M Aqua-Pure AP9000+, AP9400+ (AP9350+)
CC-QZP91G	9"	5	68 - 520 kPa	10,000 L	2 - 55°C	ZIP 91292
CC-RDMC011	10"	1	100 - 520 kPa	2,000 L	2 - 55°C	Raindance RD-CVM-68260Z
CC-RDPX051	10"	5	100 - 520 kPa	6 - 12 months	2 - 55°C	Raindance SPF68260

Aqua Cooler is a registered trademark of Aqua Cooler Pty Ltd. Aqua-Pure, Raindance and Cuno are registered trademarks of 3M Company. Comcater is a registered trademark of Comcater Pty Ltd. Everpure, Shurflo, Omnifilter and Pentek are registered trademarks of Pentair Residential Filtration, LLC. Davey is a registered trademark of Davey Water Products Pty Ltd. Zip is a registered trademark of Zip Industries.

Where line pressure exceeds 500 kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards. (Ref. AS/NZS 3500.1:2021, Clause 3.3.4).


Note:

1. No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change.
 2. This document and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems.
- Our Water Filtration Specialists can provide you with advice to suit your needs.

For more information contact your local stockist or visit us at puretecgroupp.com
 Australia **1300 140 140** | New Zealand **0800 130 140**